



# ***Yamamoto***

 Yamamoto North America



## **WUN30**

Yamamoto North America LLC  
PO Box 3264,  
205 S. Lee St.  
Bloomington, IL 61701



866-204-0519  
8am-5pm Mon-Fri Central Time  
Yamamoto-NA.com

Model No.	WUN30		
Capacity	13.6kg	30 lbs	
Drum	Diameter	Φ660 mm	Φ25.9"
	Depth	375 mm	Φ14.7"
	L/ Cubic Feet	128 L	4.5 cu.ft
Machine Size (Packing Size)	Height	1550mm (1750)	61.1" (68.9)
	Width	870mm (1070)	34.3" (42.2)
	Depth	1070mm (1270)	42.2" (50.1)
Weight of empty machine	500 kg	1103 lbs	
Crated Weight	600 kg	1323 lbs	
Drum Speed	Washing Speed	20-50rpm	
	Extraction Speed	100-800rpm / ※ <sub>1</sub> 100-750rpm	
G - Force	High Speed	236 G / ※ <sub>1</sub> 207 G	
Dynamic Loading	Frequency	15.8 Hz	
	Dynamic floor weight	1400kg/m <sup>2</sup>	328lb/ft <sup>2</sup>
Loading Door	Door Height	835 mm	32.9"
	Door Opening	φ405 mm	φ15.9"
Power	Electrical phase, Voltage, Frequency	Three-phase, AC208-230V, 60Hz /※ <sub>1</sub> Single-phase, AC208-230V, 60Hz	
	Maximum Amperage	9A	
Minimum Supply-Circuit Conductor Ampacity	15A		
Maximum Rating of Supply Circuit Overcurrent Protective Device	15A		
Motor Size	3 HP (2.2kw)		
Cold Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Hot Water Supply	Connection Port	3/4NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Detergent Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3MPa , 14.5-43.5psi , 1-3bar	
Water Drain	Connection Port	2·1/2NPT	
Steam	Supply Port	1/2NPT	
	Drain Port	3/8NPT	
	Pressure	0.4-0.6MPa , 58-87psi , 4-6bar	
Heating System	Hot Water Supply & Steam		

※<sub>1</sub> WUN30 single-phase Specification.

