



Yamamoto

 Yamamoto North America



WUN55

Yamamoto North America LLC
PO Box 3264,
205 S. Lee St.
Bloomington, IL 61701



866-204-0519
8am-5pm Mon-Fri Central Time
Yamamoto-NA.com

Model No.		WUN55	
Capacity		25.0kg	55lbs
Drum	Diameter	Φ762mm	Φ30.0"
	Depth	486 mm	19.1"
	L/Cubic Feet	221 L	7.8 cu. Ft
Machine Size (Packing Size)	Height	1565mm (1750)	61.6" (68.9)
	Width	1015mm (1200)	40.0" (47.3)
	Depth	1235mm (1400)	48.7" (55.2)
Weight of empty machine		660kg	1455lbs
Crated Weight		705kg	1555lbs
Drum Speed	Washing Speed	20-50rpm	
	Extraction Speed	100-880rpm	
G - Force	High Speed	330G	
Dynamic Loading	Frequency	14.7 Hz	
	Dynamic Floor Weight	1500kg/m2	307.2lb/ft2
Loading Door	Door Height	835 mm	32.9"
	Door Opening	Φ405mm	Φ15.9"
Power	Electrical Phase, Voltage, Frequency	Three-phase, AC208-230V, 60Hz /※2 Three - phase or Single-phase, AC208-230V, 60Hz	
	Maximum Amperage	14A/※2 16A	
Minimum Supply-Circuit Conductor Ampacity		20A	
Maximum Rating of Supply Circuit Overcurrent Protective Device		20A	
Motor Size		5HP (3.7kw)	
Cold Water Supply	Connection Port	1NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Hot Water Supply	Connection Port	1NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Detergent Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Water Drain	Connection Port	2 · 1/2NPT	
Steam	Supply Port	1/2NPT	
	Drain Port	3/8NPT	
	Pressure	0.4-0.6MPa, 58-87psi, 4-6bar	
Heating System		Hot Water Supply & Steam	
Usage Environment	Temperature of Surrounding	5-45°C , 41-113°F	
	Humidity	30-85%	
	Altitude	The machine should be installed in the altitude which is lower than in 3280 ft.	

※2 WUN55 Single-phase or Three -phase Specification.

