



Yamamoto

 Yamamoto North America



WUN70

Yamamoto North America LLC
PO Box 3264,
205 S. Lee St.
Bloomington, IL 61701



866-204-0519
8am-5pm Mon-Fri Central Time
Yamamoto-NA.com

Model No.	WUN70		
Capacity		31.8kg	70lbs
Drum	Diameter	Ø890mm	Ø35.0"
	Depth	461 mm	18.1"
	L/Cubic Feet	286 L	10.1 cu. Ft
Machine Size (Packing Size)	Height	1715mm (1900)	67.5" (74.9)
	Width	1150mm (1300)	45.3" (51.2)
	Depth	1295mm (1500)	51.0" (59.1)
Weight of empty machine		850kg	1875lbs
Crated Weight		905kg	2000lbs
Drum Speed	Washing Speed	20-50rpm	
	Extraction Speed	100-800rpm	
G - Force	High Speed	318G	
Dynamic Loading	Frequency	13.3 Hz	
	Dynamic Floor Weight	1700kg/m2	348.2lb/ft2
Loading Door	Door Height	915 mm	36"
	Door Opening	Ø475mm	Ø18.7"
Power	Electrical Phase, Voltage, Frequency	Three-phase, AC208-230V, 60Hz /※2 Three - phase or Single-phase, AC208-230V, 60Hz	
	Maximum Amperage	20A/※2 22A	
Minimum Supply-Circuit Conductor Ampacity		30A	
Maximum Rating of Supply Circuit Overcurrent Protective Device		30A	
Motor Size		7.5HP (5.5kw)	
Cold Water Supply	Connection Port	1NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Hot Water Supply	Connection Port	1NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Detergent Cup Water	Connection Port	1/2NPT	
	Water Supply Pressure	0.1-0.3MPa, 14.5-43.5psi, 1-3bar	
Water Drain	Connection Port	2 · 1/2NPT	
Steam	Supply Port	1/2NPT	
	Drain Port	3/8NPT	
	Pressure	0.4-0.6MPa, 58-87psi, 4-6bar	
Heating System		Hot Water Supply & Steam	
Usage Environment	Temperature of Surrounding	5-45°C , 41-113°F	
	Humidity	30-85%	
	Altitude	The machine should be installed in the altitude which is lower than in 3280 ft.	

※2 WUN70 Single-phase or Three -phase Specification.

